




019-420-66-011/012

Netrack standing server cabinet
42U/600x600mm - glass door

019-420-66-011/012




- 1. GLASS FRONT DOOR
- 2. HOLE FOR FAN UNIT INSTALLATION
- 3. VENTILATION HOLES
- 4. TOP BACK CABLE ENTRY
- 5. ANGLE MOUNTING BRACKET BAR
- 6. MOUNTING SPARE RACK PROFILE
- 7. SIDE PANEL
- 8. STEEL REAR DOOR

RACK DISTANCES

NETRACK STANDARD	383MM
MAXIMUM	527MM
MINIMUM	167MM

SECTION A-A
- TOP COVER VIEW


019-420-66-011/012



1. GROUND CONECTION BOLT IN THE DOOR
2. ADJUSTABLE FEET
3. VENTILATION HOLES
4. BOTTOM CENTRAL CABLE ENTRY
5. ANGLE MOUNTING BRACKET BAR
6. MOUNTING SPARE RACK PROFILE
7. SIDE PANEL
8. STEEL REAR DOOR
9. 2" CASTOR WHEELS

SECTION C-C

019-420-66-011/012




- 1. GLASS FRONT DOOR
- 2. BOTTOM FRONT CABLE ENTRY
- 3. VENTILATION HOLES
- 4. TOP/BOTTOM BACK CABLE ENTRY
- 5. ANGLE MOUNTING BRACKET BAR
- 6. MOUNTING SPARE RACK PROFILE
- 7. SIDE PANEL
- 8. STEEL REAR DOOR
- 9. BOTTOM CENTRAL CABLE ENTRY
- 10. 2" CASTOR WHEELS
- 11. ADJUSTABLE FEET
- 12.SIDE PANEL LOCK INSTALLATION SPACE

RACK DISTANCES

NETRACK STANDARD	383MM
MAXIMUM	527MM
MINIMUM	167MM

SECTION D-D


019-420-66-011/012



- 1. GLASS FRONT DOOR
- 2. ADJUSTABLE FEET
- 3. VENTILATION HOLES
- 4. FRONT DOOR LOCK INSTALLATION SPACE

FRONT ELEVATION


019-420-66-011/012



- 1. STEEL REAR DOOR
- 2. ADJUSTABLE FEET
- 3. VENTILATION HOLES
- 4. REAR DOOR LOCK INSTALLATION SPACE

REAR ELEVATION


019-420-66-011/012



- 1. SIDE PANEL
- 2. ADJUSTABLE FEET
- 3. VENTILATION HOLES
- 4. SIDE PANEL LOCK INSTALLATION SPACE
- 5. 2" CASTOR WHEELS

SIDE ELEVATION

019-420-66-011/012



- 1. VENTILATION HOLES
- 2. TOP BACK CABLE ENTRY

TOP ELEVATION