Netrack patch panel 19" 24-port cat.6 FTP, with shelf



Product price:

PLN153.73 tax included

Product codes:

Reference: 104-07 EAN13: 5908268777526 UPC: -

Product features:

Basic dimensions: 19 "/ 1U Category / Class: 6 / E Type: FTP / STP Height [mm]: 44.45 Width [mm]: 482.6 Depth [mm]: 100 Weight [kg]: 1.48 Height of the packed product [mm]: 500 Width of the packed product [mm]: 125 Depth of the packed product [mm]: 55 Weight of the packed product [kg]: 1.58 Number of ports: 24 RJ 45 Standard Rack: 19 " Height U: 1U Color: black Color code: RAL 9005

Product short description:

Check out our range of 10" and 19" patch panels, UTP, FTP and STP. We have been providing solutions for computer networks for over 25 years. Trust our experience and choose patch panels of the highest quality that will help you build a fast and reliable network.

Product description:

The network patch panel has RJ45 connectors . The contacts of the connectors are gold-plated. They ensure the highest quality of work for >1200 cycles. The device ensures fast and reliable connection of devices to the computer network. The sockets are compatible with all types of patch cords terminated with RJ45 plugs (e.g. CAT5E, CAT 6, CAT 6A, CAT7). The best effect is obtained by using patch cords of the same category as the device or higher.

Network Patch Panel LSA IDC

The Network Patch Panel has **LSA IDC** connectors on the back of the housing. Connectors are color coded for TIA 568A and TIA 568B connection types. They provide the highest quality of work for >300 installation cycles. Compatible with all popular network cable standards (e.g. CAT5e, CAT6, CAT6A, CAT7). The best effect is obtained using patch cords of the same category as the device or higher.

Network Patch Panel LSA IDC

It is possible to use 22-26AWG wires.

The most important features

- the highest quality of workmanship
- gold-plated contacts with high parameters
- construction ensuring convenient assembly and use
- space for port descriptions

Technical parameters

- category/class 6/E
- FTP/STP type
- number of ports 24 x RJ45
- RACK standard 19"
- durability of the RJ-45 connector 4000 cycles

- LSA joint durability 300 cycles
- width 19"/482.6mm
- height 1U/44.45mm
- depth 100mm
- weight [kg] 1.48

Packaging

- dimensions 125/500/55mm
- weight [kg] 1.58
- content patch panel, cable ties

see also

- patchcords
- rack screws
- organizers
- shelfs
- hanging wardrobes
- 19" standing server cabinets
- patch knife
- subscriber outlets
- LAN cable twisted pair

Product attributes: