# Netrack wall cabinet F-Line Rack 19", 12U/600x600mm - gray, glass doors, opening sides



# Product price: PLN489.00 tax included

# Product codes:

Reference: 019-120-66-021 EAN13: 5908268778967 UPC: -

# **Product features:**

Basic dimensions: 19 "/ 12U Load capacity: 80 kg Front door: glazed with a lock Rear: steel cover, removable Height [mm]: 639 Width [mm]: 600 Depth [mm]: 600 Weight [kg]: 27.55 Height of the packed product [mm]: 650 Width of the packed product [mm]: 620 Depth of the packed product [mm]: 210 Weight of the packed product [kg]: 29.05 Rack rails: 4 Rack rail position adjustment: any position to the full extent Product assembled / requires assembly: requires assembly - easy, intuitive assembly Possibility to install fans: 2x 120x120mm (105x105mm) fan, 19 "ventilation panel Youtube video id: zBy2DZsUKFU Color: gray Color code: RAL 7035 Wardrobe line: F-Line

#### **Product short description:**

Hanging rack cabinets - a professional solution for installing computer networks. Organize and secure your home or business network. Rack 19" the most universal system for installing devices for various applications. It gives the possibility of extensive expansion and configuration. F-Line is a line of cabinets that guarantees the best service parameters. Stable construction, 4 rack rails, open sides guarantee reliability and comfort in the most demanding installations.

#### **Product description:**

The most important features of cabinets rack 19" hanging F-Line

- stable and durable construction
- Easy and quick assembly
- holes for convenient wall mounting
- ventilation openings in the roof and floor for natural ventilation and for optional installation of fans (roof) (100-005-001-100) with a thermostat (100-005-001-022)
- removable side panels for convenient access to devices
- possibility of locking the possibility of opening the side panels from the outside through an internal lock
- possibility of installing optional locks in the side panels. (119-000-000-003)
- 4 rack rails ensuring safe installation of larger devices and giving the possibility of mounting smaller devices in 2 planes. E.g. a power panel behind a switch or patch panel
- wide range of rail position adjustment
- a wide selection of carefully selected and matched accessories
- the possibility of mounting the door as right or left

- door opening 220°°
- tempered glass door
- the possibility of taking a picture of the back wall
- openings in the floor and roof for cable entry

#### Technical parameters:

- product line: F-Line
- basic dimensions 19"/12U
- height [mm] 639
- width [mm] 600
- depth [mm] 600
- back: closed, can be opened
- side opening: yes, lock o from the inside, lock option
- number of rack rails: 4
- rack rails adjustment: yes, fully adjustable
- possibility of mounting fans: yes, 2x120x120mm (105x105mm)
- Libra [kg] 27.55
- carrying capacity [kg]: 80
- color: gray RAL 7035
- Manufacturing standards: Compliance with ANSI/EIA RS-310-D, DIN41491 PART1, IEC297-2, DIN41494 PART7, GB/T3047.2-92
- Compatibility with standards: ETSI metric and international 19". Adaptation to general parameters 10" no standard.

Packaging:

- packaging dimensions: 620/210/650mm
- weight in the package: 29.05 kg

Contents of the package:

- floor/roof 2 pcs.
- sides 2 pcs.
- front door 1 pc.
- rear cover 1 pc.
- frame 2 pcs.
- rack rails 4 pcs.
- door lock with keys
- Rack screws 15 sets
- Screws for assembly

# Product details

- Mark Netrack
- product line: F-Line
- EAN 5908268778967
- Index 019-120-66-021

# See also:

- shelf max, depth 450mm
- Rack screws
- ventilation panels and thermostats
- wire organizers
- 19" PDU power strip

- patch panels
- other accessories for RACK cabinets

All available product lines:

- F-Line, 19", 6-18U open sides, removable back, 4x rack rail, to be assembled.
- S Line, 10 and 19", 4.5-9U open back, 2x RACK rail, rigid, welded construction, ready to install.
- ECO Line, 19" 4-9U, open back, 2x RACK rails, to be assembled. The most economical solution.
- V-Line, 19" 2-3+4U, vertical mounting. The only cabinets with a minimum depth of 120mm to accommodate 19" devices.

Comparision table:

#### **Product attributes:**