Netrack RJ45 patch cord, molded sheath, cat. 5e UTP, 5m black



Product price:

PLN6.94 tax included

Product codes:

Reference: BZPAT5UK EAN13: 5908268771432 UPC: -

Product features:

Category / Class: 5e / D Type: UTP Weight [kg]: 0.107 Height of the packed product [mm]: 240 Width of the packed product [mm]: 170 Depth of the packed product [mm]: 50 Weight of the packed product [kg]: 0.11 Length [m]: 5 Color: black

Product short description:

See our offer **of UTP, FTP, F/UTP patch cords**. We have been providing solutions for computer networks for over 25 years. Rack cabinets , patch panels, patch cords, 10" and 19" RACK accessories - all in one proven place.

Product description:

Making an RJ45 patch cord

- **Connectors:** 2x RJ45 plug [8p8c]
 - plug body transparent polycarbonate
 - contacts gold-plated phosphor bronze, coating thickness 6μm
- **Plug cover** : molded with elastic latch protection. the cover is the width of the plug, which guarantees the possibility of connecting even with densely located ports
- Latch Cover: Helps and secures the latch when pulling wire through narrow openings
- **Conductor:** 4 x 2 x 24AWG, stranded CCA
- **Connection type:** straight 1:1 (according to the 568B standard)
- **Plug cover:** molded with elastic latch protection. the cover is the width of the plug, which guarantees the possibility of connecting even with densely located ports
- Latch Cover: Helps and secures the latch when pulling wire through narrow openings

Patch cord technical parameters

- durability: 2000 cycles
- category/class 5e/D
- UTP type
- transmission frequency 100 MHz
- transmission speed 1-GBASE-T
- length 5 m
- width 11.6 [mm]
- height 16.3 [mm]
- weight: 0.107 kg
- Performance standards: ISO/IEC 11801, PN-EN 50173-x, ANSI/TIA-568-D, ISO9001, ISO14001, OHSAS18001

Contents of the package

- Patch cord 1 pc.
- dimensions of the packed product: H/W/D 240/170/50mm
- weight with packaging: 0.11 kg

Product details

• Netrack brand

see also

- patch panels organizers RACK cabinets

Product attributes: