
Netrack server case microATX/ATX/eATX, 482*177*530mm, 4U, 19"

Product price:

**PLN636.08 tax
included**



Product codes:

Reference: NP5104
EAN13: 5908268778196
UPC: -

Product features:

Basic dimensions: 19 " / 4U

Height [mm]: 177

Width [mm]: 482

Depth [mm]: 530

Weight [kg]: 12.0

Height of the packed product [mm]: 655

Width of the packed product [mm]: 525

Depth of the packed product [mm]: 245

Weight of the packed product [kg]: 12.4

Height U: 4

Recommended minimum 19 " [mm] rack depth: 800 (minimum recommended 700)

Motherboard formats: EATX, ATX, micro ATX, mini ITX

Max. plate dimensions: 12 "x13"

Place for power supply: PS-2 ATX PSU

Number of internal bays: 8x3.5 "

Number of external bays: 3x5.25 "or 2x5.25" + 1x3.5 "

Expansion card slots: 7 x full height

Top ventilation duct: 2 x 80x80mm fan
Fans fitted: 1x120x120mm + 3x80x80mm
Space for additional fans: 2x60x60mm
Dust filter: replaceable
Material - housing: durable and stiff 1mm SGCC steel
Fabric - front: durable and stiff 1mm SGCC steel
Fabric - handles: steel / ABS
Housing color (front, sides, top): black
Housing color (interior, rear, bottom): silver galvanized
The color of the handles: black

Product short description:

A server case that allows you to configure the largest servers and computers.

Product description:

Rack server case with a height of 4 U and a depth of 530mm. Allows you to mount the largest EATX format motherboards and smaller. Provides space for 8 3.5" devices inside and 3 places 5.25/3.5" with access from the outside of the case. Allows you to mount up to 7 full-height PSI expansion cards. Properly designed cooling and ventilation system. In order to ensure proper working conditions for devices installed in the Rack housing, the distances enabling proper ventilation (min. 150mm) and the appropriate ambient temperature must be maintained. In industrial applications, attention should be paid to dust and chemical contamination. **Rack server housing** is designed for building servers and computers working in offices, warehouses, server rooms, industrial and production plants.

Rack server case - the most important information

- housing type: 19" rack , 4U
- sizes of boards to be mounted: EATX, ATX, micro ATX, mini ITX
- number of external bays: 3x5.25" or 2x5.25"+1x3.5"
- number of internal bays: 8x3.5"
- recommended depth of 19" Rack cabinet: 800mm (minimum 700mm)

Rack server case - systems and devices

Rack 19" server enclosures are most often configured with:

- servers supporting sales systems
- servers supporting warehouse and accounting systems

-
- application servers
 - database servers
 - database and application servers
 - servers and computers supporting production processes
 - print servers supporting processes on multiple printers

The most important features

- convenient installation, operation and service
- very good working conditions for server components
- ventilation openings on 2 or 3 sides of the housing
- possibility of mounting in 19" Rack racks
- the possibility of mounting slide rails to pull out the housing: NP5114
- only for models NP5104 and NP5105:
 - replaceable dust filter
 - key-locked housing

Execution

- housing: durable and rigid SGCC 1mm steel
- handles: steel/ABS
- front: durable and rigid SGCC 1mm steel
- housing color (front, sides, top): black
- housing color (inside, back, bottom): silver zinc
- handle color: black

Rack server case - technical parameters

- dimensions (width/height/depth): 482/177/530mm
- weight: 12 kg
- recommended depth of 19" Rack cabinet: 800mm (minimum 700mm)
- Motherboard format: EATX, ATX, micro ATX, mini ITX
- maximum motherboard dimensions: 12"x13"
- power adapter: none
- space for power supply: PS-2 ATX PSU
- number of internal bays: 8x3.5"
- number of external bays: 3x5.25" or 2x5.25"+1x3.5"
- expansion card slots: 7 x full height
- upper ventilation duct: 2 x 80x80mm fan
- mounted fans: 1x120x120mm + 3x80x80mm
- space for additional fans: 2x60x60mm
- dust filter: replaceable
- indicators: Power, HDD
- switches: Power, Reset
- front sockets: 2 x 2.0 USB (3.0 - option)
- security: lockable

-
- working temperature: 0-50°C

Contents of the package

- folded housing packed in a cardboard box with protection
- screws and mounting hardware
- fans (mounted in the housing)
- wires for connecting fans, switches and indicators
- dimensions of the packed product: H/W/D 245/525/655mm
- weight with packaging: 12.4 kg

see also

- sliding rails for sliding the housing out: NP5114
- Rack screws 4 pcs
- Rack screws 50pcs.
- matching 19" hanging cabinets: none - such a large enclosure requires a cabinet with the recommended depth of 700mm
- matching 19" server cabinets, standing: 700mm (recommended 800)
- power supplies for server cases
- fans
- dust filters

Product attributes: