

---

# Netrack mini-ITX/microATX server case, 482\*88.8\*390mm, 2U, 19"

## Product price:

**PLN373.03 tax  
included**



## Product codes:

Reference: NP5107  
EAN13: 5908268779100  
UPC: -

## Product features:

Basic dimensions: 19 "/ 2U

Height [mm]: 88.8

Width [mm]: 482

Depth [mm]: 390

Weight [kg]: 6.4

Height of the packed product [mm]: 535

Width of the packed product [mm]: 525

Depth of the packed product [mm]: 175

Weight of the packed product [kg]: 6.6

Height U: 2

Recommended minimum 19 " [mm] rack depth: 550 (minimum recommended 600)

Motherboard formats: micro-ATX, mini-ITX

Max. plate dimensions: 9.6 "x9.6"

Place for power supply: PS-2 ATX PSU

Number of internal bays: 2x3.5 "

Number of external bays: 2x5.25 "

Expansion card slots: 4 x low profile

---

Top ventilation duct: front / rear ventilation  
Fans fitted: 2x80x80mm  
Space for additional fans: lack  
Dust filter: constant  
Material - housing: durable and stiff 1mm SGCC steel  
Fabric - front: durable and stiff 1mm SGCC steel  
Fabric - handles: aluminum / steel  
Housing color (front, sides, top): black  
Housing color (interior, rear, bottom): silver galvanized  
The color of the handles: black

### **Product short description:**

2U server case - the best, optimal solution for many applications

### **Product description:**

**Rack server case** with a height of 2U and a depth of 390mm. Allows you to mount micro ATX, mini ITX motherboards. Provides space for 2 3.5" devices inside and 2 places 5.25 with access from the outside of the housing. Allows mounting up to 4 PSI low profile expansion cards. A properly designed cooling and ventilation system. To ensure proper working conditions for devices installed in the housing, they must be distances allowing for adequate ventilation (min 150mm) and appropriate ambient temperature. In industrial applications, attention should be paid to dust and chemical pollution. The **Rack server enclosure** is intended for building servers and computers working in offices, warehouses, server rooms, industrial and production plants.

Rack server case - the most important information

- enclosure type: 19" rack, 2U
- sizes of boards to be mounted: micro ATX, mini ITX
- number of external bays: 2x5.25"
- number of internal bays: 2x3.5"
- recommended depth of 19" Rack cabinet: 550mm (minimum recommended 600mm)

Rack server case - systems and devices

Rack 19" server enclosures are most often configured with:

- servers supporting sales systems
- servers supporting warehouse and accounting systems

- 
- application servers
  - database servers
  - database and application servers
  - servers and computers supporting production processes
  - print servers supporting processes on multiple printers

The most important features of the Rack server case

- convenient installation, operation and service
- very good working conditions for server components
- ventilation openings on 2 or 3 sides of the housing
- possibility of mounting in 19" Rack racks
- the possibility of mounting slide rails to pull out the housing: NP5115
- only for models NP5104 and NP5105:
  - replaceable dust filter
  - key-locked housing

Execution

- housing: durable and rigid SGCC 1mm steel
- handles: aluminum/steel
- front: durable and rigid SGCC 1mm steel
- housing color (front, sides, top): black
- housing color (inside, back, bottom): silver zinc
- handle color: black

Rack server case - technical parameters

- dimensions (width/height/depth): 482/88.8/390mm
- weight: 6.4 kg
- recommended depth of 19" Rack cabinet: 550mm (minimum recommended 600mm)
- motherboard format: micro ATX, mini ITX
- maximum motherboard dimensions: 9.6"x9.6"
- power adapter: none
- space for power supply: PS-2 ATX PSU
- number of internal bays: 2x3.5"
- number of external bays: 2x5.25"
- expansion card slots: 4 x profiles
- upper ventilation channel: front/rear ventilation
- mounted fans: 2x80x80mm
- space for additional fans: none
- dust filter: permanent
- indicators: Power, HDD
- switches: Power, Reset
- front sockets: 2 x 2.0 USB (3.0 - option)

- 
- security: lockable
  - working temperature: 0-50°C

#### Contents of the package

- folded housing packed in a cardboard box with protection
- screws and mounting elements
- fans (mounted in the housing)
- wires for connecting fans, switches and indicators
- dimensions of the packed product: H/W/D 175/525/535mm
- weight with packaging: 6.6 kg

see also

- slide rails for sliding the housing out: NP5115
- Rack screws 4 pcs
- Rack screws 50pcs.
- matching 19" wall cabinets: 550mm (minimum recommended 600)
- matching 19" server cabinets, standing: 600mm
- power supplies for server cases
- fans
- dust filters

#### **Product attributes:**